SW-1W/1WR





SPECIFICATIONS

Model	SW-1W/1WR				
Max.capacity	1/2kg	2.5/5kg	4/10kg	10/20kg	15/30kg
Readability	0.5/1g	1/2g	2/5g	5/10g	5/10g
Maximum tare	-0.9995	-2.499	-3.998	-9.995	-14.995
Internal resolution	1/60,000				
External resolution	1/2,000 ~ 1/3,000				
Display digit	5 Digit (SW-1W), 6 Digit (SW-1WR)				
Display type	LCD (SW-1W), LED (SW-1WR)				
Operating temperature	-10℃ ~ 40℃				
	Dry battery (D type x 6ea) or 9V DC adapter				
Power	9V DC adapter (SW-1W only)				
	Pb battery,12V DC adapter (SW-1WR only)				
Battery life	Approx. 400hours or 800hours (Alkaline battery)				
	Approx. 30hours (SW-1WR)				
Platter size (mm)	247(W) x 195(D)				
Dimensions (mm)	278(W) x 317(D) x 141(H)				
Product weight	3.7kg				

1/2,000~1/3,000 dual interval resolution for better accuracy

 The SW-1W/1WR adopts dual interval technology, allowing for an automatic change of the SW-1W/1WR interval for an even more precise reading.



Dust & Waterproof digital scale (Level IP 66)

 The SW-1W/1WR can be protected from water, dirt and other external agents.



Rechargeable Battery operation (SW-1WR only)

• The SW-1WR can be used for up to 30 hours after charging the battery.




Clear and Highly legible LED display (SW-1WR only)

• SW-1WR Series has a 19mm LED display and uses 6 highly legible digits.



DIMENSIONS



OPTIONS

- Rear display (Dual display)
- 9V DC adapter (SW-1W only)
- 12V DC adapter (SW-1WR only)





Adapter can be different foreach country *